

MOTOR PERFORMANCE		Winding codes	RC	RC	UC	UC
		UNIT	FREE AIR COOLING	FORCED AIR COOLING	FREE AIR COOLING	FORCED AIR COOLING
Fp	Peak force	N	2400	2400	2290	2290
Fc	Continuous force	N	354	383	340	367
Fs	Standstill force	N	268	289	257	277
Ip	Peak current	Arms	53.3	53.3	110	110
Ic	Continuous current	Arms	7.78	8.39	16.1	17.4
Is	Standstill current	Arms	5.88	6.33	12.2	13.1
vs	Rated low speed	mm/s	0.50	0.98	0.51	1.0
Pc	Power dissipation @ Ic	W	230	265	229	264
Fd	Max. detent force (average to peak)	N	0.0	0.0	0.0	0.0
Fa	Attraction force	N	0.00	0.00	0.00	0.00

MOTOR SETTING		UNIT				
Kt	Force constant	N/Arms	47.3	47.3	21.8	21.8
Ku	Back EMF constant (*)	Vrms/(m/s)	28.4	28.4	13.1	13.1
Km	Motor constant	N/√W	28.9	28.9	27.8	27.8
R20	Electrical resistance at 20°C (*)	Ohm	1.78	1.78	0.411	0.411
L	Electrical inductance (*)	mH	3.99	3.99	0.851	0.852
rth	Thermal time constant	s	1290	653	1260	629
Rth	Thermal resistance	K/W	0.477	0.413	0.480	0.415
2tp	Magnetic period	mm	64	64	64	64
mw	Magnetic way mass	kg/m	22.7	22.7	22.7	22.7
mm	Motor mass	kg	1.50	1.95	1.45	1.90

MOTOR ENVIRONMENT		UNIT				
Udc	Nominal DC bus voltage	VDC	600	600	600	600
Ss	Stator exchange surface	m²	0.24	0.24	0.24	0.24
x	Assumed stroke	m	0.89	0.89	0.89	0.89
θamb	Ambient temperature	°C	20	20	20	20
θmax	Maximum coil temperature	°C	130	130	130	130
θa	Inlet air temperature	°C	N/A	20	N/A	20
qa	Minimum air flow	l/min	N/A	66	N/A	66
Δpa	Minimum inlet air gauge pressure	bar	N/A	0.9	N/A	0.9

Notes: (*) terminal to terminal.
Hypotheses and tolerances are in ETEL Integration Manual.

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

